

Full Colour Multi Function Printer

**RICOH**  
imagine. change.

# RICOH IM C6500 IM C8000

☑ Copier ☑ Printer ☑ Facsimile ☑ Scanner



RICOH  
IM C6500

65  
200%

Monochrome  
Full Colour

RICOH  
IM C8000

80  
200%

Monochrome  
Full Colour

### GENERAL

Functions	Copy, Print, Scan, Fax
Operation Panel	10.1" Smart Operation Panel
Warm-up time	40 Seconds
First Output Speed : B/W	5.5 - 4.8 Seconds
First Output Speed: Full Color	7.5 - 6.4 seconds
Continuous output speed	65 - 80ppm
CPU	Intel Apollo Lake Processor 1.6GHz
Memory	4GB standard/maximum
HDD	640GB standard/maximum
Weight (Mainframe)	250kg or less
Dimensions (W x D x H)	Standard: 750 x 883 x 1225 mm
Power Source	220-240V, 50/60Hz

### ECOLOGY

Power consumption: Maximum	Less than 2400W
Power consumption: Ready	191 - 203 W
Power consumption: Sleep mode	0.79 W
TEC Value	1.201 - 1.651 kWh

### COPIER

Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400% in 1% steps

### SCANNER

Scanning Speed B/W	120ipm (Simplex) / 240ipm (Duplex)
Resolution	1200 dpi maximum
Compression method	TIFF (MH, MR, MMR, JBIG2) Grayscale, JPEG (Colour)
File Formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High Compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multipage High compression PDF, Multipage PDF/A
Scan modes	E-mail, Folder USB, SD Card, URL, FTP SMB

### PRINTER

Printer Language	Standard : PCL5c, PCL6, PostScript3, PDF Direct Option : XPS, Genuine Adobe PostScript 3", IPDS, PDF Direct from Adobe
Print resolution	Maximum: 1200 x 4800 dpi
Network interface	Standard: Ethernet 10- baseT/100 base-TX/1000 base-T, USB Host Type A, USB Device I/F, SD Slot, NFC tag, USB Device (TypeB: 1 Port)
Network interface	Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11 a/b/g/h), PJ4 I/F (Only Copy Connect), Ethernet Print only RJ-45 network port
Windows environments	Windows 7/8. 1/10, Windows Server 2008/2008R/2012/2012R2/2016/2019
Mac OS environments	Macintosh OS X v 10.12 or later
UNIX environments	UNIX Sun, Solaris UNIXSun , Solaris, HP-UX, SCO Open Server, RedHat Linux, IBM AIX, Citrix XenApp, XenDesktop
SAP environments	SAP R/3, SAP S/4

### FAX

Circuit	PSTN, PBX
Transmission speed	G3: approximately 2 secs (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission) G3: approximately 2 secs (200 x 100 dpi, MMR, ITUT #1 chart TTI off, memory transmission)
Modem speed	33.6 Kbps maximum
Resolution	Standard mode: 8 x 3.85 line/mm, 200 x 100 dpi Detail mode: 8 x 7.7 line/mm. 200 x 200 dpi Super fine mode: 8 x 15.4 line/mm, 16 x 15.4) line/mm, 400 x 400 dpi (with optional SAF memory)
Compression method	MH, MR, MMR JBIG
SAF memory size	Standard: 4MB   Maximum: 60MB

### PAPER HANDLING

Recommended paper size	SRA3+, SRA3, A3, A4, A5, A6, B4, B5, B6
Paper input capacity	Standard: 3700 sheets Maximum: 8100 sheets
Paper output capacity	Standard: 500 sheets Maximum: 3500 sheets
Paper weight	Standard Trays: 52.3 - 256g/m2 Bypass: 52.3 - 300g/m3, Duplex 52.3 - 256 g/m3
Paper Types	Plain paper, Recycle Paper, Color paper, Special Paper 1-3, Letterhead, Bond Paper, Preprinted, Prepunched, Cardstock

# THINK COPIER CALL V COPIER

03 4280 2285 | 012 719 2285 | 017 627 2285

www.vcopier.com.my